





# SHUTTLE 4

CLASSY WITH 4-PERSON SEATING

Comfortable, quiet and smooth, the E-Z-GO® Shuttle™ 4 seats four with a spacious cargo deck for luggage and belongings. Designed to enhance the professionalism and style of your resort or club, the Shuttle™ 4 can be equipped with a wide range of options and accessories to meet your business-specific requirements.

COLOR OPTIONS 360° ENLARGE

ELECTRIC SPECS

GAS SPECS

WHERE TO BUY

## GAS SPECS

VIEW ALL SPECS [ + ]

CUSTOMIZE MY E-Z-GO

### Body & Chassis [ - ]

<b>Frame</b>	Welded steel with DuraShield™ powder coating
<b>Front Body &amp; Finish</b>	Injection-molded TPE (Thermoplastic Elastomer)
<b>Rear Body &amp; Finish</b>	Injection-molded TPE (Thermoplastic Elastomer)
<b>Standard Color</b>	Champagne
<b>Seat Pod</b>	Fiberglass and gelcoat finish

STANDARD FEATURES

### Dimensions [ - ]

<b>Overall Length</b>	133 in (338 cm)
<b>Overall Width</b>	46.5 in (119 cm)
<b>Overall Height (no canopy)</b>	48.6 in (123 cm) (top of steering wheel)
<b>Overall Height (with canopy)</b>	72 in (183 cm)
<b>Wheel Base</b>	93.5 in (237 cm)
<b>Front Wheel Track</b>	34.2 in (86.7 cm)
<b>Rear Wheel Track</b>	38 in (97 cm)
<b>Ground Clearance (at differential)</b>	4.3 in (11 cm)
<b>Cargo Box Width (inside)</b>	42.5 in (108 cm)
<b>Cargo Box Length (inside)</b>	32 in (80 cm)
<b>Cargo Box Depth (inside)</b>	11.5 in (29 cm)
<b>Cargo Box Capacity</b>	9 cu ft (0.25 m3)
<b>Cargo Box Material</b>	Wood stake sides

OPTIONS/ACCESSORIES

### Power [ - ]

<b>Power Source</b>	4 cycle, 21 ci (350 cc)
<b>Valve Train</b>	Twin cylinder OHV
<b>Horsepower (kW)</b>	11 hp (8.2 kW)
<b>Electric System</b>	Starter/generator, solid state regulator
<b>Batteries (qty/type)</b>	One 12-volt, maintenance-free
<b>Key or Pedal Start</b>	Pedal start
<b>Air Cleaner</b>	Dry cartridge with remote intake
<b>Lubrication</b>	Pressurized oil system
<b>Oil Filter</b>	Washable permanent filter
<b>Cooling System</b>	Air cooled
<b>Fuel Capacity</b>	5.8 gallons (22.8 L)
<b>Drive Train</b>	Automatic, continuously variable transmission (CVT)
<b>Transaxle</b>	Differential with helical gears
<b>Gear Selection</b>	Forward-reverse
<b>Rear Axle Ratio</b>	13:32:1

OTHER MODELS

### Performance [ - ]

<b>Seating Capacity</b>	4-person
<b>Dry Weight</b>	1010 lb (460 kg)

<b>Bed Load Capacity</b>	400 lb (180 kg)
<b>Outside Clearance Circle</b>	25.5 ft (7.8 m)
<b>Ground Speed (level ground)</b>	13 mph $\pm$ 0.5 mph (21 kph $\pm$ 0.8 kph)
<b>Steering and Suspension</b> [ - ]	
<b>Steering</b>	Self-compensating rack and pinion
<b>Front Suspension</b>	Leaf springs with hydraulic shock absorbers
<b>Rear Suspension</b>	Leaf springs with hydraulic shock absorbers
<b>Service Brake</b>	Rear wheel mechanical self-adjusting drum
<b>Parking Brake</b>	Self-compensating single-point engagement
<b>Front Tires</b>	Turf 18 x 8.50-8 (4-ply rated)
<b>Rear Tires</b>	Turf 18 x 8.50-8 (4-ply rated)