





# SHUTTLE 6

MAXIMUM SPACE, 6-PERSON SEATING

Created for larger resorts, hotels and airports, the Shuttle 6 provides the ultimate in convenient transportation. The vehicle features seating for six and a 1200 lb capacity. With a 48-volt DC electric drivetrain or a 13 hp Kawasaki® gas engine, the Shuttle 6 provides the power and reliability needed to guarantee efficiency.

COLOR OPTIONS 360° ENLARGE

ELECTRIC SPECS

GAS SPECS

WHERE TO BUY

## GAS SPECS

VIEW ALL SPECS [ + ]

CUSTOMIZE MY E-Z-GO

### Body & Chassis [ - ]

Frame	Welded steel with DuraShield™ powder coating
Front Body & Finish	Injection-molded TPE (Thermoplastic Elastomer)
Rear Body & Finish	Injection-molded TPE (Thermoplastic Elastomer)
Standard Color	Champagne
Seat Pod	Fiberglass and gelcoat finish

STANDARD FEATURES

### Dimensions [ - ]

Overall Length	133 in (338 cm)
Overall Width	46.5 in (119 cm)
Overall Height (no canopy)	48.6 in (123 cm) (top of steering wheel)
Overall Height (with canopy)	72 in (183 cm)
Wheel Base	93.5 in (237 cm)
Front Wheel Track	34.2 in (86.7 cm)
Rear Wheel Track	38 in (97 cm)
Ground Clearance (at differential)	4.3 in (11 cm)

OPTIONS/ACCESSORIES

### Power [ - ]

Power Source	4 cycle, 21 ci (350 cc)
Valve Train	Twin cylinder OHV
Horsepower (kW)	11 hp (8.2 kW)
Electric System	Starter/generator, solid state regulator
Batteries (qty/type)	One 12-volt, maintenance-free
Key or Pedal Start	Pedal start
Air Cleaner	Dry cartridge with remote intake
Lubrication	Pressurized oil system
Oil Filter	Washable permanent filter
Cooling System	Air cooled
Fuel Capacity	5.8 gallons (22.8 L)
Drive Train	Automatic, continuously variable transmission (CVT)
Transaxle	Differential with helical gears
Gear Selection	Forward-reverse
Rear Axle Ratio	13:32:1

OTHER MODELS

### Performance [ - ]

Seating Capacity	6-person
Dry Weight	1010 lb (460 kg)
Curb Weight	1045 lb (475 kg)
Vehicle Load Capacity	1200 lb (540 kg)
Outside Clearance Circle	25.5 ft (7.8 m)
Ground Speed (level ground)	13 mph ± 0.5 mph (21 kph ± 0.8 kph)

### Steering & Suspension [ - ]

Steering	Self-compensating rack and pinion
----------	-----------------------------------

<b>Service Brake</b>	Rear wheel mechanical self-adjusting drum
<b>Parking Brake</b>	Self-compensating single-point engagement
<b>Front Tires</b>	Turf 18 x 8.50-8 (4-ply rated)
<b>Rear Tires</b>	Turf 18 x 8.50-8 (4-ply rated)

